




## Bamboo – Slats



TOP VIEW



SIDE VIEW




PERSPECTIVE

PRE-DRILL A HOLE IN THE NODE—THE THICKEST PART OF THE BAMBOO STRIP—AND SCREW IT ONTO YOUR STRUCTURE. WOOD PUTTY MIXED WITH A LITTLE BAMBOO SAW DUST WORKS WELL TO HIDE THE SCREW. A PNEUMATIC NAIL GUN CAN BE USED AS WELL.

### NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.amaZuluinc.com](http://www.amaZuluinc.com)



BAMBOO

BAMBOO SLATS