

1239 Commons Court
 Clermont, FL 34711
www.amazuluinc.com



(352)243-5309
 (352)243-5361

Multi-Width Faux Slate Specification Chart

Shingle Dimensions

Widths	12", 10" 9", 7", 6"	Thickness at Butt	1/2"
Length	18"	Thickness at Tip	1/8"

Hip - Ridge - Starter

	6" Hip & Ridge (for ridge vents only)	7" Hip & Ridge (standard)	12" Starter
Pieces / Bundle	20	20	20
Lineal Ft / Bundle	5*	5*	20
Pieces / Lineal Ft	4*	4*	1

*At recommended 6" exposure Note: 9" pieces available for ridge; 4" pieces available for turrets.

Field Shingles per Roofing Square

Coursing	Roof Pitch	Max. Exposure	Bundles / Square	Shingles / Square	Weight / Square
Straight	6:12 or greater	7.5"	7.00	210	273 lbs
Staggered	6:12 or greater	7.0"	7.50	225	293 lbs
Straight or Staggered	Less than 6:12	6.0"	8.75	262	342 lbs

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Straight coursing may be used at any exposure up to 7.5" and staggered coursing may be used at any exposure up to 7.0".

Packing and Shipping Information

	# Shingles	Weight
Per Bundle*	30	39 lbs
Per Pallet**	1,440	1,872 lbs
Per Truckload***	34,560	44,928 lbs

* All weights are approximate ** 48 bundles per pallet ** 24 pallets per truckload

Testing Summary

Type of Test	Standard	Results
Fire Test	ASTM E 108	Class A
Impact Test	UL 2218	Class 4
Wind Test	ASTM D 3161	Certified to 110MPH*

Building Code Approvals: ICC-ES ESR-2119, Miami Dade County, FL NOA No. 06-308.03 Exp. 7/12/12 and TDI

1239 Commons Court
Clermont, FL 34711
www.amazuluinc.com



(352)243-5309
(352)243-5361