

1239 Commons Court
 Clermont, FL 34711
www.amazuluinc.com



(352)243-5309
 (352)243-5361

Multi-Width Faux Cedar Shake Specification Chart

Shingle Dimensions

Widths	9", 8", 7", 6", 4"	Thickness at Butt	5/8"
Length	22"	Thickness at Tip	1/4"

Hip - Ridge - Starter

	6" Hip & Ridge (standard)	One-piece Hip & Ridge	12" Valley Shingle	12" Starter
Pieces / Bundle	20	10	10	20
Lineal Ft / Bundle	8.33*	8.33*	4.3*	20
Pieces / Lineal Ft	2.40*	2.40*	2.3*	1

* At recommended 10" exposure

Field Shingles per Roofing Square

Coursing	Roof Pitch	Max. Exposure	Bundles / Square	Shingles / Square	Weight / Square
Straight	4:12 or greater	10"	8	200	304lbs
Staggered	4:12 or greater	9"	9	225	342lbs

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Felt interlay is suggested on any pitch and required on pitches less than 6" in 12"

Packing and Shipping Information

	# Shingles	Weight
Per Bundle*	25	38lbs
Per Pallet**	1,200	1,824lbs
Per Truckload***	28,800	43,776lbs

* All weights are approximate ** 48 bundles per pallet ** 24 pallets per truckload

Testing Summary

Type of Test	Standard	Results
Fire Test	ASTM E 108	Class A or Class C*
Impact Test	UL 2218	Class 4
Wind Test	ASTM D 3161	Certified to 110MPH*

* See amaZulu Installation Instructions for details.